# Declaration of Performance
# UK CONSTRUCTION PRODUCTS (AMENDMENT ETC) (EU EXIT) REGULATIONS 2020

**DoP Number:**

JL1025

**1. Unique identification code of the product-type:**

JL1062,JL1063 Architectural range 2.5" & 3"
Oval Dead locks

**2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the UK CPR:**

JL1062,JL1063 Architectural range 2.5" & 3"
Oval Dead locks

**3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:**

For use on fire and smoke compartmentation doors, when fitted in accordance with the manufacturer's fitting instructions.

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):**

JEDO
Unit 10 Mitcham Industrial Estate , Mitcham, Surrey CR4 2AP , United Kingdom

**5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**

N/A

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in UK CPR, Annex V:**

System 1

**7. In case of the declaration of performance concerning a construction product covered by a designated standard:**

EN 12209: 2003 incorporating Corrigendum N° 1 UK Approved product certification body No. (Fill in the Approved Body number below) performed the determination of the product type on the basis of type testing (including sampling); initial inspection of the manufacturing plant and of the factory production control and continuous surveillance; assessment and

evaluation of factory production control; and issued the certificate of constancy of performance of the product.

| Enter Approved Body Number Here |
| --- |
| 1121 |

**8. UK Technical Assessment:**

N/A

**9. Declared performance**

| **Essential characteristic**<br>**Self closing** | **Performance** | **Designated technical specification** |
|---|---|---|
| 5.4.2 Closing force | Grade 1, Up to 100 kg door mass, 50 N max. closing force | EN 12209: 2003 incorporating Corrigendum N° 1 |
| 5.1.2 Re-latching force of latch bolt | Deadlock – N/A | |
| **Essential characteristic**<br>**Durability of self closing** | **Performance** | **Designated technical specification** |
| 5.3.1 Durability of latch action | Deadlock – N/A | EN 12209:2003 incorporating Corrigendum N° 1 |
| Ability to maintain the door in the closed position and not contribute to the spread of fire | Grade 1 | |
| **Dangerous Substances Annex ZA3** | The materials in the product(s) do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations. | |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Andrew McMeechan

Product development

Date of issue: 04/07/2022

Unit 10 Mitcham Industrial Estate
Mitcham, Surrey CR4 2AP
United Kingdom

---

This Declaration of Performance is issued on a standard template provided by the GAI for use in the door and hardware industries. There is no implied endorsement of the content, which is the responsibility of the issuing company.

The Guild of Architectural Ironmongers
BPF House, 6 Bath Place, Rivington Street, London, EC2A 3JE
Tel: +44 (0) 20 7033 2480 | Fax: +44 (0) 20 7033 2486